

(Govt. Sponsored)

Post: Raniganj, Dist.: Paschim Bardhaman, Pin- 713347 ESTD - 1957

Date: 01/03/2022

TENDER NOTICE

This is an open circulation on behalf of T.D.B College, Raniganj seeking competitive quotations from potential companies/ agencies/ vendors for the Supply, Installation & Commissioning of the following items:

Sl. No.	Description	Quantity
1	Mitutoyo Vernier Calliper Model No: 531-122 Measuring Range: 0-150 mm Accuracy: 0.05mm Lower/Upper Scale: 0.05mm inch	02
2	Mitutoyo Vernier Calliper Model No: 530-119 Measuring Range: 0-300 mm Accuracy: 0.04 mm Resolution: 0.001 inch Lower/Upper Scale: 64/27.5 mm	02
3	TDS Meter	04
4	EstWing Hammer , 22 oz. Pointed Tip ROCK PICK	01
5	Digital pH Meter	02
6	Pocket pH Meter	02
7	Abney's Level	03
8	Clinometers Analog, Diameter: Up to 180 mm	04
9	Munsell Soil Colour Chart	01
10	Brunton Compass	02
11	Standard False Colour Composite Map LISS-IV CARTOSAT-I CARTOSAT-II	02 02 02
12	Tracing Paper 100 GSM A4 size	1000 sheets
13	Tracing Paper 100 GSM A3 size	1000 sheets



(Govt. Sponsored)

Post: Raniganj, Dist.: Paschim Bardhaman, Pin- 713347 ESTD - 1957

14	Tracing Graph Paper 100 GSM A4 size	500 sheets
15	Log-Log Graph Paper 100 GSM A4 size	500 sheets
16	Digital Sound Level Meter 30dB - 130 dB Resolution: 0.1 dB Frequency: 31.5 Hz to 8,000 Hz	
17	Arsenic Testing Kit Type: Compact Testing Type: Manual Range: 0-1000 ppb Number of Tests: 100	100
18	 Digital Soil and Water Testing Kit pH Resolution: 0.01 pH. pH Accuracy: ±0.01 pH ± 1 Digits Temperature Compensation: 0-100 deg C. Conductivity Range: 0-20 mS. Conductivity Resolution: 10 μS (0.01 mS). Conductivity Accuracy: ±05 % FS ± 1 Digit. Temperature Range: 0 to 100 deg C. Temperature Accuracy: ±0.1°C ± 1 Digits Temperature Sensor: Semi Conductor Type TDS Range: 0-20 ppt. TDS Accuracy: ±0.5 % FS ± 1 Digit. DO Range: 0-20 ppm. DO Resolution: 0.1 ppt. DO Accuracy: 0.5 ppm ± 1 Digits. DO Sensor: Gold / Silver Aerometric. Turbidity Range: 0-1000 NTU. Turbidity Resolution: 1 NTU. Turbidity Accuracy: ±3 % ± 1 Digits. Sample System: 30 mm Clear Glass. Salinity Range: 0-50 ppt. 	01
19	Soil sample packet A. 4×6 in: 1000 pc B. 8×10 in: 1000 pc Colour: Transparent Opening type: Zip lock Material: Plastic	01
20	Freeman 100-meter measuring tape ■ □Width: 13 mm ■ □Reel: Open	03



(Govt. Sponsored)

Post: Raniganj, Dist.: Paschim Bardhaman, Pin- 713347 ESTD - 1957

21	Case material: Acrylonitrile Butadiene Styrene Yellow fiberglass Red fiberglass Alloy steel	01 01 01
22	Trowel • Plate Material: Steel • Handle Material: Wood	04
23	Steel Spade Plate Material: Steel Handle Material: Wood Handle Length: 18-24 inch	02
24	 Electronic Weighing Balance Weighing Capacity: Upto 220 gm Material to be measured: Metals, Chemical, Organic Accuracy: 0.001gm Platform Dimensions: 80mm diameter Readability(g): 0.001 Linearity error(g): ≤±0.2 Reproducibility(g): ≤0.1 Pan Size: 115 phi Power supply: 220V/6F22ND 9V Power: AC/DC dual Display: LCD Model: TL210 Brand: TOPLAB 	01
25	Waterproof Portable Dissolved Oxygen and BOD Meter Weight: 400 gm (14.2 oz.) Brand: V TECH Automation Grade: Automatic Logging Type: Log-on-demand Logging Memory: up to 400 samples Automatic Shut-Off: User selectable: 5, 10, 30, 60 minutes or disabled Environment: 0 to 50 Deg C (32 to 122 Deg F); RH 100% (Ip67) Dimensions: 185 x 93 x 35.2 mm	01



(Govt. Sponsored)

Post: Raniganj, Dist.: Paschim Bardhaman, Pin- 713347 ESTD - 1957

	 GARMIN Handheld GPS Device Usage/Application: Handheld Model Name/Number: Etrex 32x Type: Wireless Display Resolution: 240 x 320 pixels Internal Memory and Micro SD Card: 8 GB Battery Life: 25h 	
	 Unit Weight: 5 oz (141.7g) with Batteries Brand: Garmin Display size: 3.5 x 4.4 cm×5.6 cm Display Type: 2.2" transflective, 65K color TFT Battery Type: 2 AA NiMH or Lithium 	
26	 Water Rating: IPX7 Interface: Mini USB MAP Segments: 3000 Birdseye: 250 BirdsEye Imagery files External Memory Storage: yes (32 GB max microSD (TM) card) 	01
	 Waypoint Favorites Locations: 2000 Tracks: 200 Track Log: 10000 Points And 200 Saved Tracks Routes: 200 Routes, 250 Points per Route And 50 Points Auto Routing Compass: Yes (Tilt-Compensated 3-Axis) Geochaching Friendly: Yes (Paperless) Custom Maps Compatible: Yes (100 Custom Map Tiles) Wireless Connectivity: Yes (ANT+) 	



(Govt. Sponsored)

Post: Raniganj, Dist.: Paschim Bardhaman, Pin- 713347 ESTD - 1957

27	PM 2.5 Monitor Brand: Precise Display Type: LCD Colour: Blue Automation Grade: Automatic Weight (kg): 0.80 Material: ABS Packing with LCD Packing Type: Corrugated Box Size: 225mmx70mmx20mm Accuracy (micron): 2.5 Micron Number of Sensors: 3 Measuring principle: Laser scattering Range of PM2.5 detection: 0-999.9 µg/m3 Resolution of PM2.5: 0.1 µg/m3 Range of PM10 detection: 0-999.9µg/m3 Resolution of PM10: 0.1 µg/m3 Minimum of particle diameter: 0.3 µm Relative Accuracy: ±20% or ±15µg/m3 MAX Auto power off: 5 minutes after no push button, the meter automatically enterto power off mode Power: 7.4V Li-ion Battery capacity: 1400mAh Power Adapter: 9V Charging current: 2.0A Working time Approximate: 30 hours Working temperature: -20-70	01
28	 Mortar and pestle (Hand) Colour: White, Black Base Shape: Round Marble Type: Porcelain Thickness: 5 to 20 mm Weight: 400-800 gm Brand: Johnson, EISCO, AGATE, AMBER 	08
29	Polarizing Petrographic Microscope Type of Product: Led Coaxial Laboratory Microscope Voltage: 100-200 V Colour: White Illumination: Halogen Illumination Material: Metal • □ Model No: MXL Magnification: 40x - 1500x Optical Tube: Binocular Brand: Weswox	01



(Govt. Sponsored)

Post: Raniganj, Dist.: Paschim Bardhaman, Pin- 713347 ESTD - 1957

30	Polarized Microscope Body: Rugged, single die cast, ergonomic design, touch point treated Optical system: Strain free achromatic universal optical system, colour corrected, anti-fungal, anti-bacterial coated (multi-layered hard coated) Transmitted Illumination: Koehler halogen/LED, intensity adjustable, battery backup, auto cut-off Incident Illumination: LED/halogen with aperture and field diaphragm Polarizing Facilities: Polarizer mounted below the condenser Analyzer: Analyzer with scale removable from optical path, rotatable, focusable & centerable bertrand lens Retarding Plates: λ Plate, 1/4 λ(Mica) & Quartz Wedge Viewing Head: Monocular/Binocular/Trinocular Head Nosepiece: Reverse centerable quadruple/quintuple M25 x 0.75 threads with multiple ball-bearing, rubber/metal Grip & click stop Eyepiece: Extra wide field with diopter adjustment Objectives: POL Plan, S-APO/APO, Infinite objectives Mechanical Stage: Graduated large circular rotary stage Condenser: Abbe with iris diaphragm & filter slot. Brightfiled, polarizing Focusing: Coaxial (low position), both side, coarse & Fine with tension control & upper limit stopper Attachment: Slots for Compensator Plates Switchable orthoscopic/conoscopic Certification: EU CE, ISI, ISO, TUV	01
31	Laboratory Thermostatic Drying Oven Capacity: 100-500 Kg Max Temperature: 500 Degree F Material: Mild Steel Shape: Rectangle Automation Grade: Automatic Frequency: 50 Hz Heating Power: 2 HP Volume: 96 Cu Ft Inner Dimension: 48 x 48 x 72 Inch Outer Dimension: 67 x 86 x 83 Inch Speed: 3300 CFM Brand: Labtech Instruments	04
32	Chisel edge geological hammer • Weight: 1 kg	04
33	Simon's Rain Gauge	02
34	Open Series Topographic Map	50
35	Globe with light in centre facility	01
36	Rock Specimen Set	01



(Govt. Sponsored)

Post: Raniganj, Dist.: Paschim Bardhaman, Pin- 713347 ESTD - 1957

Date: 01/03/2022

37	Mineral Specimen Set	01
38	Rocksmins Minerals Specimen Slides Thin Section	01
39	Digital Theodolite	02
40	Test Tube (25x20 mm), Borosilicate Glass	Pack of 50pc
41	Beaker ■ 100 ml ■ 250 ml ■ 500 ml	20 20 20
42	Blotting Paper (150 mm X 250 mm) Rectangular	500 sheets
43	Rotameter Manual	30
44	Barometer	01
45	Hygrometer	01
46	Maximum-Minimum Thermometer	01
47	Distilled Water 25 ltr.	01
48	Water Sample Bottle Size: 400 ml Material: Glass Colour: Transparent Cap type: Screw type Shape: Cylindrical	50
49	Water Sample Bottle Size 100 ml Material: Polypropylene Colour: Transparent Cap type: Screw type Shape: Cylindrical	50
50	Logitech MK200 Media Corded Keyboard and Mouse Combo	02
51	Logitech M90 Wired USB Mouse 1000 DPI Optical Tracking, Black	02
52	MK345 Wireless Keyboard and Mouse Combo	01

Interested Vendors may contact College office for further clarification. Sealed quotations must be submitted within 10 days from the date of publication of this notice.

Sd/-**Principal** T.D.B College, Raniganj